

In the claims:

1. (Currently Amended) A complex of structural elements for forming glass brick walls, comprising:

- a substantially C-shaped aluminium profile bar (2) for perimetally bounding the wall,
- a plurality of dividers (6) horizontally separating each glass brick from the adjacent one and having at least their exposed longitudinal edges of aluminium,
- a plurality of horizontal aluminium stringers (4) consisting of a horizontal web (14) provided at least along one longitudinal edge with a T-shaped appendix (18), said web being provided at regular intervals with seats for fixing uprights of said dividers, said stringers being provided at their ends (22) with coupling elements to be removably coupled to the interior of the vertical C-shaped profile bars,

characterised in that the central web (14) of the horizontal stringer is provided at its ends with cylindrical portions (16) for fixing the coupling elements by screws.

2. (Currently Amended) A complex as claimed in claim 1, ~~characterised in that~~ wherein the coupling elements consist of a substantially rectangular element which has its minor sides (24) faceted and comprises slotted holes (26) of curved extension said sides consisting of a flat portion (28) and a curved portion (30), the distance between the flat portions being substantially equal to the distance between the facing cavities formed by the ribs (10) of the profile bar (2).

3. (Currently Amended) A complex as claimed in claim 1, ~~characterised by~~ further comprising a bar (36) provided in one of its minor sides with slotted holes (38) terminating with an eyelet (40) through which pins (42) are inserted, to be axially engaged in

said holes by nuts 44, and are locked by their threaded ends in holes provided in the edges of the horizontal stringer 4.

4. (Currently Amended) A complex as claimed in claim 1 ~~claims 1 and 3, characterised by~~ further comprising an H-shaped profile bar, the flanges of which embrace two back-to-back C-shaped profile bars (2), and which is also provided with two U-shaped appendices (48) which when assembled form a seat (50) for the insertion of a head (52) provided at the end of a pin (54), said pin (54) engaging with slotted holes (38) of the bar (36).

5. (Currently Amended) A complex as claimed in claim 4, ~~characterised in that~~ wherein the side walls of the C-shaped profile bars present an inner surface provided with two pairs of ribs (10), each rib being provided on that surface facing the other rib with an engagement tooth (12).

6. (Currently Amended) A complex as claimed in claim 1, ~~characterised in that~~ wherein the stringer fixing seats consist of holes (20) for engagement by pins (34) which also engage the ends of the divider uprights.

7. (Currently Amended) A complex as claimed in claim 1, ~~characterised in that~~ wherein the divider consists of ladder-shaped plastic spacers (56) provided at their ends with coupling elements (58), the vertical portions (60) of which are shaped to snap-engage in an aluminium profile bar (60).

8. (Currently Amended) A complex as claimed in claim 1 ~~characterised in that~~ wherein each divider and/or each stringer are made of wood and are provided at their ends with two seats for the snap engagement of an aluminium T-shaped appendix.

9. (Currently Amended) A complex as claimed in claim 1
~~characterised in that~~ wherein the stringers comprise a
longitudinal groove ~~(64)~~ housing a rubber gasket retaining the
glass brick.